

Insulationsleeve

FITCO® Iso-PUR-HT-Insulationsleeve

All-purpose black protective and modified insulating hose made of polyurethane with very good UV resistance.

Operating temperature: - 40°C to + 150°C
Standard colour: Matt-Black
 Other colours on request

Description	Inner diameter (mm)	Tolerance ID (mm)	Wall thickness (mm)	Tolerance wall thickness (mm)
FITCO® Iso-PUR-HT 1.5x0.3mm	1.6	+ 0.3	0.3	± 0.1
FITCO® Iso-PUR-HT 2.0x0.3mm	2.1	+ 0.3	0.3	± 0.1
FITCO® Iso-PUR-HT 2.5x0.3mm	2.6	+ 0.3	0.3	± 0.1
FITCO® Iso-PUR-HT 3.0x0.3mm	3.1	+ 0.3	0.3	± 0.1
FITCO® Iso-PUR-HT 3.5x0.4mm	3.6	+ 0.3	0.4	± 0.1
FITCO® Iso-PUR-HT 4.0x0.4mm	4.1	+ 0.3	0.4	± 0.1
FITCO® Iso-PUR-HT 4.5x0.4mm	4.6	+ 0.3	0.4	± 0.1
FITCO® Iso-PUR-HT 5.0x0.5mm	5.1	+ 0.3	0.5	± 0.15
FITCO® Iso-PUR-HT 5.5x0.5mm	5.6	+ 0.3	0.5	± 0.15
FITCO® Iso-PUR-HT 6.0x0.5mm	6.1	+ 0.3	0.5	± 0.15
FITCO® Iso-PUR-HT 6.5x0.5mm	6.6	+ 0.3	0.5	± 0.15
FITCO® Iso-PUR-HT 7.0x0.6mm	7.1	+ 0.3	0.6	± 0.15
FITCO® Iso-PUR-HT 7.5x0.6mm	7.6	+ 0.3	0.6	± 0.15
FITCO® Iso-PUR-HT 8.0x0.6mm	8.1	+ 0.3	0.6	± 0.15
FITCO® Iso-PUR-HT 9.0x0.6mm	9.1	+ 0.4	0.6	± 0.15
FITCO® Iso-PUR-HT 10x0.6mm	10.1	+ 0.4	0.6	± 0.15
FITCO® Iso-PUR-HT 11x0.6mm	11.1	+ 0.4	0.6	± 0.15
FITCO® Iso-PUR-HT 12x0.6mm	12.1	+ 0.4	0.6	± 0.15
FITCO® Iso-PUR-HT 13x0.8mm	13.1	+ 0.5	0.8	± 0.15
FITCO® Iso-PUR-HT 14x0.8mm	14.1	+ 0.5	0.8	± 0.15
FITCO® Iso-PUR-HT 15x0.8mm	15.1	+ 0.5	0.8	± 0.15
FITCO® Iso-PUR-HT 16x0.8mm	16.1	+ 0.6	0.8	± 0.15
FITCO® Iso-PUR-HT 17x0.8mm	17.1	+ 0.6	0.8	± 0.15
FITCO® Iso-PUR-HT 18x0.8mm	18.1	+ 0.6	0.8	± 0.15
FITCO® Iso-PUR-HT 19x0.8mm	19.1	+ 0.6	0.8	± 0.15
FITCO® Iso-PUR-HT 20x1.0mm	20.1	+ 0.6	1.0	± 0.2
FITCO® Iso-PUR-HT 21x1.0mm	21.1	+ 0.6	1.0	± 0.2
FITCO® Iso-PUR-HT 22x1.0mm	22.1	+ 0.7	1.0	± 0.2
FITCO® Iso-PUR-HT 23x1.0mm	23.1	+ 0.7	1.0	± 0.2
FITCO® Iso-PUR-HT 24x1.0mm	24.1	+ 0.7	1.0	± 0.2
FITCO® Iso-PUR-HT 25x1.0mm	25.1	+ 0.7	1.0	± 0.2
FITCO® Iso-PUR-HT 26x1.0mm	26.1	+ 0.7	1.0	± 0.2
FITCO® Iso-PUR-HT 27x1.0mm	27.1	+ 0.7	1.0	± 0.2
FITCO® Iso-PUR-HT 28x1.0mm	28.1	+ 0.8	1.0	± 0.2
FITCO® Iso-PUR-HT 29x1.0mm	29.1	+ 0.8	1.0	± 0.2
FITCO® Iso-PUR-HT 30x1.0mm	30.1	+ 0.8	1.0	± 0.2

*Other sizes on request

GREMCO GmbH · Sterzinger Str. 6 · D-86165 Augsburg · T +49.821.272.63-0 · F +49.821.272.63-44 · info@gremco.de · www.gremco.de •
 PDS No.: 20230818114501 Version: UWM0823-0 Print Date: 18. Aug. 2023

FITCO® = trademark of GREMCO
 All of the above information is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. GREMCO make no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. GREMCO's only obligations are those in the Standard Terms and Conditions of Sale for this product, and in no case will GREMCO be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use or misuse of the product.

Insulationsleeve

FITCO® Iso-PUR-HT-Insulationsleeve

Packaging: On spools, cut lengths or printed tubing on request.

Properties	Test Method	Typical Value
Mechanical		
Tensile strength	DIN 53504	≥ 35 MPa
Ultimate elongation	DIN 53504	> 700 %
Tear resistance	DIN 53515	> 100 N/mm
Voltage value 100%	DIN 53504	7 MPa
Abrasion	DIN 53516	< 40 mm ³
Specific density	DIN 53479	1.20 ± 0.05 g/cm ³
Hardness Shore A	DIN 53505	85 ± 2
Chemical		
Ozone resistance	VDE 472 - 805	Pass

Vorteile:

- UV-resistant
- Ozone resistant
- Hydrolysis resistant
- Microbe resistant
- Cadmium free
- Lead-free
- Mercury-free
- Chromium-free