

Expandable Braided Sleeving

FITCOFLEX®-B-2PA/PET

Protective sleeve manufactured using PET (Polyester) and PA66 (Polyamide 6.6) monofilaments.

Description:

FITCOFLEX®-B-2PA/PET has a open weave structure which permits drainage and prevents condensation. This sleeve is ROHS and REACH compliant and halogen free.

Manufactured using 0.25mm PET and PA66 monofilaments, FITCOFLEX®-B-2PA/PET offers very good abrasion resistance and is particularly suited to the protection of pipes, hoses and cable harnesses. It offers outstanding protection against oil, fuel and other chemical agents. FITCOFLEX®-B-2PA/PET has a expandable and flexible construction.

Specification:

Meets the requirements of PSA D441959/B CAT D. Independent test reports (SGS RES 217215 05A / 05B) available upon request.

FITCOFLEX-B-PA/2PET also meets the requirements of RENAULT D441959/B CAT C4. Independent test reports (SGS RES 217215 05A-2) available upon request.

Operating temperature: - 40°C to + 150°C

Standard color: Black
Other colors on request



Description	Diameter (mm)	
	Nominal Size	Maximum Diameter
FITCOFLEX-B-2PA/PET 3	3	8
FITCOFLEX-B-2PA/PET 5	5	13
FITCOFLEX-B-2PA/PET 10	10	17
FITCOFLEX-B-2PA/PET 15	15	25
FITCOFLEX-B-2PA/PET 20	20	33
FITCOFLEX-B-2PA/PET 25	25	40
FITCOFLEX-B-2PA/PET 30	30	48

*Other sizes on request

Packaging: On spools or cut lengths.