

Braided hose

FITCOFLEX®-B-PA25

Protective sleeve with an open weave structure manufactured using polyamide 6.6 (PA6.6) monofilaments.

Description:

FITCOFLEX®-B-PA25 is ROHS and REACH compliant and halogen free. Manufactured using 0.25mm PA6.6 monofilaments, FITCOFLEX®-B-PA25 offers very good abrasion resistance and is particularly suited to the protection of pipes, hoses and cable harnesses. It offers outstanding protection against oil, fuel and other chemical agents. FITCOFLEX®-B-PA25 has a tough, lightweight and flexible construction.

Specification:

Meets the requirements of PSA D441959/B CAT C. Independent test reports (SGS RES 217215 02A / 02B) available upon request.

Operating temperature: - 40°C to + 125°C

Standard colour: Black
Other colours on request



Description	Dimensions (mm)		
	Nominal Size	Min. Diameter	Max. Diameter
FITCOFLEX-B-PA25 2	2	2.0	3.5
FITCOFLEX-B-PA25 3	3	3.0	6.0
FITCOFLEX-B-PA25 4	4	3.0	6.5
FITCOFLEX-B-PA25 5	5	4.5	8.5
FITCOFLEX-B-PA25 6	6	5.0	9.5
FITCOFLEX-B-PA25 8	8	6.5	12.0
FITCOFLEX-B-PA25 10	10	8.0	14.0
FITCOFLEX-B-PA25 12	12	9.0	18.0
FITCOFLEX-B-PA25 14	14	9.0	19.0
FITCOFLEX-B-PA25 16	16	9.0	21.0
FITCOFLEX-B-PA25 18	18	12.0	25.0
FITCOFLEX-B-PA25 20	20	16.0	28.0
FITCOFLEX-B-PA25 22	22	18.0	30.0
FITCOFLEX-B-PA25 25	25	19.0	32.0
FITCOFLEX-B-PA25 30	30	21.0	36.0
FITCOFLEX-B-PA25 40	40	28.0	48.0
FITCOFLEX-B-PA25 50	50	36.0	60.0
FITCOFLEX-B-PA25 60	60	42.0	68.0

Special sizes on request