

Braided Sleeving

FITCOFLEX®-B-PETNVH

FITCOFLEX®-B-PETNVH is a flexible and lightweight high quality NVH (Noise/Vibration/Harshness) protective sleeve made of polyethylene terephthalate monofilament and multifilament. The sleeve offers outstanding abrasion protection for hoses / pipes and wire harnesses against mechanical damage. The special construction provides excellent noise reduction / acoustic dampening properties and is particularly suited to automotive applications.

FITCOFLEX®-B-PETNVH offers outstanding resistance against oils, liquids, fuel, and various chemical agents and thus can extend the life time of the protected components.

Operating temperature: -70°C to +150°C
Standard color: Black
 Other colors on request
Material: Polyethylene Terephthalate (PET)



Description	Diameter (mm)	
	Nominal Size	Maximum Diameter
FITCOFLEX-B-PETNVH 3	3	8
FITCOFLEX-B-PETNVH 5	5	13
FITCOFLEX-B-PETNVH 10	10	17
FITCOFLEX-B-PETNVH 15	15	25
FITCOFLEX-B-PETNVH 20	20	33
FITCOFLEX-B-PETNVH 25	25	40
FITCOFLEX-B-PETNVH 30	30	48

Packaging: On spools or cut lengths.

Key benefits:

- Operating temperature up to +150°C
- NVH construction (Noise/Vibration/Harshness)
- Lightweight
- Fluid and chemical resistance

FITCO® = trademark of GREMCO
 All of the above information is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. GREMCO make no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. GREMCO's only obligations are those in the Standard Terms and Conditions of Sale for this product, and in no case will GREMCO be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use or misuse of the product.