

Expandable Braided Sleeving

FITCOFLEX®-B-PET25

Protective sleeve manufactured using PET (Polyester) monofilaments.

Description:

FITCOFLEX®-B-PET25 is a superior quality abrasion sleeve, suitable for a wide range of applications particularly within the automotive industry. This sleeve is ROHS and REACH compliant, halogen free and self-extinguishing. Manufactured using 0.25mm PET monofilaments, FITCOFLEX®-B-PET25 offers excellent abrasion resistance and is particularly suited to the protection of pipes, hoses and cable harnesses. It offers outstanding protection against oil, fuel and other chemical agents. FITCOFLEX®-B-PET25 has a tough, lightweight and flexible construction.

Specification:

Meets the requirements of PSA D441959/B CAT C. Independent test reports (SGS RES 217215 02A) available upon request.

Operating temperature: - 70°C to + 150°C

Standard color: Black
Other colors on request



Description	Diameter (mm)	
	Nominal Size	Maximum Diameter
FITCOFLEX-B-PET25 3	3	8
FITCOFLEX-B-PET25 5	5	13
FITCOFLEX-B-PET25 10	10	17
FITCOFLEX-B-PET25 12	12	22
FITCOFLEX-B-PET25 15	15	25
FITCOFLEX-B-PET25 18	18	28
FITCOFLEX-B-PET25 20	20	33
FITCOFLEX-B-PET25 25	25	40
FITCOFLEX-B-PET25 30	30	48

*Other sizes on request

Packaging: On spools or cut lengths.