

FEP-Shrink tubing

FITCOTUBE® FT-FEP

Chemical resistant and sterilizable shrink tubing made from modified FEP which shrinks even at low temperatures. Protection against high heat, humidity and corrosion. Particularly suitable for the automotive, medical and aerospace industries.

Transparent alternative to PTFE-tubing.

Operating temperature: up to +200°C

Shrink temperature: + 215°C

Shrink ratio: 1,6: 1

Standard colour: Transparent



Description	Inner diameter (mm)		Wall thickness (mm)
	as supplied (min.)	after shrinkage (max.)	after shrinkage (nom.)
FT-FEP 3/32 (2.38/1.42)	2.38	1.422	0.203
FT-FEP 1/8 (3.18/1.905)	3.18	1.905	0.254
FT-FEP 3/16 (4.76/2.921)	4.76	2.921	0.254
FT-FEP 1/4 (6.35/3.81)	6.35	3.810	0.254
FT-FEP 3/8 (9.53/5.715)	9.53	5.715	0.305
FT-FEP 1/2 (12.70/7.62)	12.70	7.620	0.381
FT-FEP 3/4 (19.05/11.43)	19.05	11.430	0.508
FT-FEP 1 (25.40/15.24)	25.40	15.240	0.635
FT-FEP 1-1/2 (38.10/22.86)	38.10	22.860	0.762
FT-FEP 2 (50.80/30.48)	50.80	30.480	0.762

Packaging: 1.2m pieces, coil goods on request.

Processing note: Care for clean and accurate cutting edge. Start shrinkage on the end.
Pre-heat metal body.